



E2-3 Plus shown

Markets Served:

- Agriculture
- Assisted Living
- Automotive
- Bio-Pharmaceutical
- Botanicals
- Bottled Water Plants
- Casinos
- Chemical Processing
- Commercial Buildings
- Dairies
- Educational Facilities
- Energy / Power / Cogeneration
- Electronics
- Government
- Grocery
- Food / Beverage
- Health Clubs
- Hotels / Lodging
- Hospitals / Healthcare
- Ink / Dye Production
- Laboratories
- Laundry
- Manufacturing
- Marine
- Military
- Multi-Unit Housing
- Municipalities
- Plating / Coating
- Printing
- Pulp / Paper
- Oil / Petroleum / Gas
- Textile
- Theme Parks
- Universities
- Vehicle Wash

The Culligan® E2 Series REVERSE OSMOSIS SYSTEM

Effective water treatment that is easy to manage.

The E2 Reverse Osmosis System is an economical water treatment solution, which reduces operating and post treatment costs. The E2 Reverse Osmosis system helps you reduce maintenance costs by reducing contaminants* from your water that affect taste and clog equipment. Control your installation costs by using a system configured for your unique needs. Keep your operating costs low with an easy-to-use electronic controller.

The E2 RO is part of the Culligan® Commercial and Industrial Solutions that combine durable and efficient equipment, systems experience, and technical experts who understand your unique requirements. From planning your system to installing your water treatment equipment, Culligan® Commercial and Industrial Solutions offer options that help deliver the quality of water to meet your needs. Consult with a Culligan® representative to create your solution.

CULLIGAN® COMMERCIAL AND INDUSTRIAL SOLUTIONS ADVANTAGES:

- Simple System Integration
- Global Product Platform
- Flexible Configurations
- Quick Delivery / Easy Installation
- Culligan® CP+ Controller

*Contaminants may not necessarily be in your water.



SYSTEM SPECIFICATIONS

Specification	US	Metric
Inlet Pressure (dynamic)	20-50 psig	1.4 – 3.5 bar
Operating Pressure, max.	120–150 psig	8.2 – 10.3 bar
Power Voltage Frequency Phase	208-230 60 Hz 1	
Feed Water Temperature	33–100° F	1–40° C
Turbidity, max.	< 1 NTU	< 1 NTU
pH Range	3 – 11	3 – 11
Chlorine, max.	0 mg/l	0 mg/l
Total Dissolved Solids, max.	2500 mg/l	2500 mg/l
Silt Density Index Well Water Surface Water	< 3 < 5	< 3 < 5
Iron, max.	< 0.1 mg/l	< 0.1 mg/l
Salt Rejection, nominal	> 98 %	> 98 %
Product Water Hardness	< 1% Raw Hardness	< 1% Raw Hardness

Examples of RO Applications

- Ice Production / Drinking Water (Reduces scaling, improves taste and clarity)
- Steam Production (Reduces scaling and maintenance)
- Humidification (Reduces scaling and dusting)
- Misting (Reduces scaling, improves taste and clarity)
- Pretreatment for High Purity Systems (Reduces regeneration requirements)
- Reclaim / Recycling (Water conservation)
- Boiler and cooling towers (Improves energy, reduces chemical consumption)
- Washing and Rinsing (Improves performance, spot-free rinses)
- Brackish water potabilization

Standard Features

- Painted Steel Frame Design
- Energy Efficient Multi-stage Stainless Steel Pump
- FRP Membrane Housings
- Inlet Solenoid Valve
- Pretreatment Sediment Filter
- Concentrate and Recirculation Throttling Valves
- Pressure Gauge
- Rotameter Style Flow Meters
- Culligan® CP+ Control Panel
 - Level Control Input
 - Pretreatment Lockout
 - Startup Flush/Timed Flush
 - Low Pressure Auto-Restart
 - Indicator Lights

Optional Features & Accessories

- Multi-Stage Pretreatment Filters
- Storage Tanks
- Level Controls
- Chemical Feed Pumps
- Ultraviolet Sterilization
- Pressurized Storage System
- Global Power Platform
- Additional Customization Available on request
- Auto Shut Down on High Product TDS

E2 Plus Reverse Osmosis System

Model	Nominal Capacity* (gpm/lpm)	Nominal Capacity* (gpd/m ³ /h)	Module Qty & Size	Nominal System Recovery (%)	Motor HP - KW	Power Req'd (VAC)	Dimension L x W x H (in – mm)
E2-2	2.8	4000	(2), 4"x40"	50	1	230V/60/1	26 x 29 x 53
	10.6	15140			0.75		660 x 737 x 1346
E2-3	4	5800	(3), 4"x40"	60	1	230V/60/1	26 x 29 x 53
	15.14	21953			0.75		660 x 737 x 1346
E2-4	5.2	7500	(4), 4"x40"	60	1	230V/60/1	26 x 29 x 53
	19.68	28388			0.75		660 x 737 x 1346
E2-5	6.3	9000	(5), 4"x40"	75	1	230V/60/1	26 x 29 x 53
	23.85	34065			0.75		660 x 737 x 1346
E2-6	6.9	10000	(6), 4"x40"	75	1	230V/60/1	26 x 29 x 53
	26.12	37850			0.75		660 x 737 x 1346

*Nominal initial capacity based on properly pretreated feed water of 500 ppm TDS, temperature of 77° F (25° C), Silt Density Index below 3.0 and an applied pressure of 140 psi. Productivity will vary depending on other feed water conditions.



www.culligan.com • 866-787-4293

For over 80 years, Culligan® has made better water. Our global network, comprised of 800+ dealers and international licensees in over 90 countries, is dedicated to addressing your water-related problems. As a worldwide leader in water treatment, our sales representatives and service technicians are familiar with the local water conditions in your area. Being global and local position us to deliver customized solutions to commercial and industrial water issues that affect your business and your bottom line.

All trademarks used herein are registered trademarks of Culligan International Company.

Products manufactured or marketed by Culligan and its affiliates are protected by patents issued or pending in the United States and other countries.

Culligan reserves the right to change the specifications referred to in this literature at any time, without prior notice.